



WBMS-3 Semi-automatic Blowing Machine



WBMS-3 and WBMS-4 Semi-automatic 3cavity and 4cavity PET blowing machine china blows PET bottle from 0.1-1.5L, neck size from 18mm-30mm.

Feature

- Double crank arm for mold locking reaches high mold-locking strength and flexible action.
- Use PLC for control (time relay control optional), easy repair, low cost, with the time controllable accurately in 0.01s.
- The gas circuit consists of moving and blowing so as to satisfy the different air demand of them.
- Far-infrared heater uses a way of conversion self-rotating heating and the rail revolution makes the heating even, quick and reliable.
- Every heating lamp has independent temperature control device to get ideal preform heating effect in this PET blowing machine china.
- Direction of the heating lamp is adjustable upon different preforms.
- Only need one operator, do not need special training. Simple installation and start.

Technical Parameter

	ITEM	UNIT	WBMS-3
PRODUCT	Theoretical output	Pcs/hr	1500
	Max. Volume	L	1.5
	Max. Height	MM	360
	Max. Diameter	MM	105
MOLDING	Number of Cavities	/	3
	Mould Plate Dimension(L×H)	MM	490*470
	Mould Thickness	MM	220
	Mould Opening Stroke	MM	180
ELECTRICAL	Power		220-380V/50-60HZ
	Total Power	KW	21
	Heating Power	KW	20
MACHINE	Main Body Dimension(L×W×H)	M	1.6×0.65×2.0
	Main Body Weight	KG	650
	Pre-heater(L×W×H)	M	1.8×0.60×1.4
	Pre-heater Weight	KG	350
	Bottle conveyor ((L×W×H)	M	2.0×0.60×1.1
	Bottle conveyor weight	KG	80