

## Shrink Tunnel Machine CE-4015A (Taiwan)



### Features:

1. Heat shrink using infrared ray heater, all kinds of shrinkable films are available for our machines.
2. The conveyer speed for heat shrink is controlled by precision electric stepless type instrument, speed is adjustable and highly stable.
3. The heat shrink model is light and small. Its legs can be dismantled easily in order to save space
4. It saves electricity and shrinks fast.
5. Adopting automatic temperature controller or constant temperature controller (according to customer need).
6. The conveyor belt for heat shrink can be made in to roll type, net type or Teflon net according to the character of the products.

### Technical Parameter:

Model	CE-4015A	CE-4520A	CE-4530S
<b>Power</b>	Single Phase, 220v 50-60Hz	Single Phase, 220v 50-60Hz	Single Phase, 220v 50- 60Hz
<b>Power Consumption</b>	5kw	6kw	9.6kw
<b>Tunnel Size (L x W x H)</b>	700 x 400 x 150mm	850 x 450 x 200mm	1000 x 450 x 300mm
<b>Packing Speed</b>	0-10 meter/min	0-10 meter/min	0-10meter/min
<b>Conveyor Size (L x W)</b>	1050mm x 400mm	1200mm x 450mm	1500mm x 450mm
<b>Machine Dimension (LxWxH)</b>	1180 x 620 x 1050mm	1330 x 720 x 1100mm	1650 x 720 x 1220mm