

## *PDV-130P Automatic Premade Bag Type Vacuum Packaging Machine With Pickles*



Applicable to duck tongue, dried egg, chicken joints, chicken legs, chicken neck, chicken feet, duck plaque, duck feet, duck legs, wing roots, wing tips, wings, two wings and other irregular materials vacuum bag packaging.

### **Feature:**

1. Applicable to single-piece, single-packaged foods such as dried bean curd and fish tofu.
2. Fast packaging speed, stable performance, high yield and high vacuum.
3. It has a waterproof system to make cleaning more convenient, it adopts a color touch electronic display, which is easy to operate.
4. The packaging machine uses prefabricated bags with perfect pattern and high sealing quality, which greatly enhances the product grade.
5. High-end equipment, atmosphere, technology, easy to manage and enhance corporate image.
6. Under the reasonable cost, innovatively solve the problem of vacuum packaging of various dried bean products.
7. The packaging speed reaches 3000 packs / hour, fully realize the efficiency of the enterprise.
8. Customers can choose different power requirements for easier use.

**Technical Data:**

<b>Machine model</b>	<b>PDV-130P</b>
Machine materials	304 stainless steel
Vacuum Pump	Germany Busch 63 pump / 2kW Shanghai Zhongde 63 pump / 1.5kW (optional)
Pneumatic Components	Japan SMC (Difficult part) Taiwan Airtac (non-standard)
Drive method	Motor drive (cam gear lever full mechanical mode)
Measurement method	Automatic, manual machine
Applicable material	Distributed as dried beans, mustard, mustard, snow, sour beans, dried tea, large dried beans, chicken rice, spicy chicken, marinated eggs, three-winged wings and other irregular materials, soy products and pickles.
work process	1. Giving bag 2. Open bag 3. filling 4. adding liquid 5. reserved 6. reserved 7. management 8. reserved → (vacuum)
	1. giving bag 2. close lid 3. first vacuum 4. second vacuum 5. third vacuum 6. fourth vacuum 7. sealing 8. sealing and cooling 9. deflation 10. Open lid and take out
Sealing method	Instantly heat the seal, and then seal it coldly to ensure the seal is beautiful.
Packing speed	35~60bag/min. (Speed is determined by product characteristics)
Bag material	Aluminum foil bag, paper bag, nylon bag and other composite film bags
Bag size	W: 50mm-130mm L: 80mm-200mm
Total power	5.5kW
Voltage	380V 50Hz
Overall size	2100mm x 1400mm x 1600mm (L * W * H), Without hoist
Machine weight	2.2T
Use environment	Room temperature 10-40 degrees 30-90% RH, no exposed, no corrosive gas, no dust and other harsh environments.