

DSL-250A Single-head Auto Shrink Sleeve Applicator Labeler



Machine Features

1. Multiple communications interfaces for Device Net, Control NET, Ethernet/IP, Provirus DP and analog for increase system compatibility.
2. No need to change the specially designed cutter plate within the rated specifications. Change of cutter plate in only three minutes.
3. Color touch panel control system ensures machine is operator friendly.
4. Forceful insertion designs can lower production costs.
5. Integrated adjustment design for the entire transmission mechanism gives you the maximum convenience for accommodating different types of label specifications.
6. Accommodates film paper core size from 5"-10" with variable adjustments.
7. With unique programmed servo speed acceleration/deceleration curve, for reducing machine wear and tear to minimum level.
8. Instead of conventional control, we adapt network based advanced communication fuzzy servo control system to increase accuracy and speed.
9. No need to adjust label or bottle sensors when changing speeds.

Specification

Max speed	250BPM
Bottle Diameters	φ25mm~φ125mm
	(Based on the bottle dimension of specification provided by the customer)
Film Material	PVC /PET /OPS
Film Width	PVC : 0.035mm~0.08mm, PET : 0.04mm~0.06mm,OPS : 0.04mm~0.06mm
Machine Size	900mm*897mm*2452mm(L*W*H)
	(Dase-Sing reserves the right to modify the apperance and dimension of the machine, in order to optimize the fuction of the requirement)
Voltage	3P;220V,380V,440V
	(According to customer requirement)