

RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine



The RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine, expertly designed for M-type bags, also known as gusset bags or square bags. This machine offers precise and efficient packaging, tailored specifically to handle these specialized pouch types. Whether you are packaging food, pharmaceuticals, or other goods, the RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine ensures high-quality results.

Description

User-Friendly Operation with the RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine

The RZ10-M190 features a user-friendly HMI and PLC control system, allowing operators to easily manage and adjust settings for optimal performance. With integrated data logging, the RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine enables you to track and analyze production data, helping to enhance efficiency and maintain quality control across your packaging operations.

Safety and Reliability of the RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine

Safety and reliability are central to the design of the RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine. The machine is equipped with a safety door, a No Bag No Fill No Seal system, and fault alarms to prevent errors and reduce waste. The RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine also includes a grooved cam system ensures accurate bag handling, while the vacuum pump and guide bar type air exhaust system guarantee effective air removal for high-quality sealing.

Maintenance Made Easy with the RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine

Designed for ease of maintenance, the RZ10-M190 includes a wipe/wash down structure, making it simple to clean and maintain. This design not only minimizes downtime but also ensures that the RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine remains reliable and efficient over the long term, providing a dependable solution for businesses focused on M-type bag packaging.

Main Specification

Model	RZ10-M190 Rotary Premade Pouch Pick Fill Seal Machine
Bag size	W: 80-190 mm; L: 80-370 mm
Filling Range	≤ 500 g
Packing Speed	≤ 55 bags/min (depending on products and bags materials)
Weight	2000 kg
Dimensions (L*W*H)	2300 mm*1950 mm*1560 mm (L W H)
Total Power	6.27 kw (Two heat seals, without vacuum pump)
Driving Power Source	380 V three-phase five line 50 HZ (other power can be customized)
Compress Air Requirement	≥ 0.5 m³/min (Compressed air is provided by the customer)