

T1650F-L Pre-stretch Pallet wrapping machine



Control System

- Photo-eye pallet height sensor
- 0-3 top (bottom)&up-down wrap times choose
- 3-12RPM variable turntable speed by frequency changer
- Variable carriage up/down speed
- Cycle pause capability

Turntable:

- Go home position after wrap cycle finished
- Soft start/soft stop
- Heavy duty chain drive Film carriage
- Friction brake(variable film tension control)
- Heavy duty chain carriage lift, calm and safety

Options:

- Ramp
- Pneumatic top plate (T1650E-CS)
- Packing height: 2800mm
- Turntable diameter: 1800mm, 2000mm
- Turntable capacity: 2500kgs, 3000kgs

Advantages:

1. Durable using, our wrapping machines can be used for super 10 years which is approved by most of our customers
2. Easy operation, we improve the machine according to 20 years experience to make it more human friendly, safe and easy operation.
3. Film head with special design:
Special design of pre-stretching film head with function of film stretching Max 300%.
With door for easy threading of film, also with film sensor to stop the machine if the film is broken.
Safety crush prevention device

Specifications:

Wrapping size :	L (500-1050) mm* W (500-1050) mm
Loads height :	1800-2400 mm
Wrapping efficiency :	20-40 loads/hour
Turntable size :	diameter 1500mm, height : 78mm
Weight capacity :	2000kg
Film carriage :	Side mount, Pre-stretch carriage, auto feeding film
Control system :	PLC programmer control system
Motor :	Turntable-0.75kw、 Film carriage-0.37kw、 Tower-0.37kw