

RM Automatic film shrink wrapping machine



This machine is designed for mineral water, fruit juice, wine, beer, infusion bottle, and other products development, strong specificity, stable performance, silent fastening after packaging, beautiful, push for the single machine.

USES the unique fission design technology, automatic sealing machine with dual cycle heat shrink machine, machine can be used, and can be used alone.

Sealing and cutting machine adopts Italian hot sealing cold cut/eager to advanced technology, fully meet international quality standards, quality more stable and reliable sealing.

Heat shrinkable machine adopts adjusting motor, invert/phone/electronic pressure regulating speed machinery, such as the different way of speed adjustment, suitable for hot shrinkage of different varieties of packaging requirements.

Heat shrinkable machine according to the binary system of hot and cold wind, channel and heat evenly, effect of shell at room temperature, the heat energy is saved, and guarantee the shrinkage effect.

Heat shrinkable machine transfer using German technology, Teflon mesh belt, the mesh belt heat slow, with fewer calories, with high temperature resistance, abrasion resistance, tensile, and many other advantages. Become a mainstream packaging industry high-grade configuration. The pneumatic components with PLC as control core, adopts mechanical synchronous control, mechanical interlock control, guarantee the safety of machine use.

By changing the molds can apply to all kinds of varieties of packaging. The machine has reasonable structure, stable framework, within a certain range of energy-efficient. Make the production safety and production efficiency improved significantly.



RM-100A



RM-150A



RM-250A



RM-A500



RM-B600



膜包机

Technical parameters

Model	RM-100A	RM-150A	RM-250A	RM-350A	RM-A500	RM-B600
Voltage	3PH 380V/50HZ					
Air source	≥ 0.5Mpa					
Oversize dimension (mm)	5850*1200*1900	5850*4000*1900	9500*1000*1920	13200*1100*2000	10000*2480*1950	10000*2480*1950
Max pack size(mm)	450*400*390	450*300*390	450*450*350	500*450*350	450*400*320	450*350*350
Capacity	5-8pack/min	8-12pack/min	12-18pack/min	18-25pack/min	6-10pack/min	3-5pack/min
Max sealing length (mm)	650	650	700	700	700	700
Power(kw)	1.8/18-22	2.2/18-22	4/22-28	4/22-28	3.6/22-28	6/22-28
Conveyor height(mm):	850	900	900	900	850	900
Suitable film/cardboard	PE				≥2mm	