

## Vertical Packing Machine KDS-520



## **Technical characteristics:**

- 1. English and Chinese screen display, operation is simple.
- 2. PLC computer system, function is more stable, adjustment any parameters not need stop machine.
- 3. It can stock ten dispose, simple to change variety.
- 4. Sever motor drawing film, position accurately.
- 5. Temperature independent control system, precision get to±1°C.
- 6. Horizontal, vertical temperature control, suitable for various of mix film, PE film packing material.
- 7. Packing type diversification, pillow sealing, standing type, punching etc.
- 8. Bag-making, sealing, packing, print date in one operation.
- 9. Work circumstance quiet, low noise.
- 10. The machine adopt servo motor control, screw measuring, precision ±1.
- 11. Adjustment product weight without any tools.
- 12. Filling head can be changed, suitable for mix film and PE film.

## **Application:**

Packing powder such as milk powder, coffee powder, flour powder etc.

## **Technical parameters:**

Model	KDS-520
Bag size	(Length):80-400(mm)
	(Width):150-250(mm)
Packing speed	5-60 (bags)/ (min)
Max film width	520(mm)
Film thickness	0.04-0.09(mm)
Pulling film type	dual belt tension membrane
Air consumption	0.8Mpa 0.4m³/min
Power source	2.2kw 220v 50Hz
Measuring range	Max5000ml
Dimension	(L)1500*(W)1140*(H)1540mm
Weight	550kg