

Auto Tablet Coating Machine KC-series



Feature:

- Perfect flat coating on tablets by the main body of airtight chamber
- Film, aqua and sugar coating in a machine
- Easy control and monitoring using PLC by touch screen
- Reduced loss of coating solution by using HVLP type spray gun with high transfer efficiency
- External attachment of the spray gun arm for easy spray gun control and maintenance
- Distribution and discharge of desired amounts due to full discharging by detachable suit
- Extended space due to electric and air pressure parts installed inside the machine
- The air supply part installed in the left of pan directly supplies hot wind to the surface of tablet and it passes through tablet tumbled by baffle and hole in the pan and goes out through dust collecting hood installed on the outer wall of pan, so no heat quantity is lost and optimum coating is possible in a short time.

Specifications:

Model		KC100FS	KC130FS	KC150FS	KC170FS	KC200FS
Pan dia.(mm)		1005	1300	1500	1700	2000
Working volume(ℓ)		105	225	350	560	900
Output capacity(kg)		50-95	120-200	200-250	320-400	500-650
Drive motor(kw)		2.2	3.7	5.5	7.5	11
Pan speed(r.p.m)		1-10	1-10	1-10	1-10	1-10
Dimension	W(mm)	1,5	1,6	1,8	1,98	2,5
	D(mm)	1,52	1,73	1,9	2,25	2,7
	H(mm)	1,9	1,95	2,14	2,33	2,8