



## *HTD-series Post Bin Blender*



HTD Series Post bin blender is mainly used in blending of solid particle and dust powder materials in pharmaceutical industry. With features of being easy in loading and discharging and having good blending effects it is also widely used in food and chemical industries.

### **Features:**

- A. The bin is slippery inside easy to clean and has no dead angles complying with GMP requirements.
- B. Feeding valve is equipped with anti-disoperation device reliably sealed and easy to be removed and cleaned.
- C. With PLC and touch screen integrated speed controlled by frequency variation this machine has many features such as adjustable rotating speed and working parameter automatic positioning printing and fault alarming.
- D. It takes less floor space and is therefore flexible and convenient during installation.
- E. It is easy in bin replacing.

## Technical Parameters:

Model	Main dimensions						Volume	Net Loading	Speed	Power	Power	Weight
							(L)	capacity				
	L	W1	W2	H	H1	H2		(KG)	rpm	Kw	Kw	T
<b>HTD-50</b>	2000	1100	650	1900	200	650	50	25	3-25	1.1	1.1	0.7
<b>HTD-100</b>	2050	1200	650	1900	200	650	100	50	3-25	1.1	1.1	0.8
<b>HTD-150</b>	2100	1350	650	2000	250	650	150	75	3-20	1.1	1.1	0.9
<b>HTD-200</b>	2200	1800	800	2200	250	650	200	100	3-20	1.5	1.5	1
<b>HTD-300</b>	2400	2000	800	2400	300	700	300	150	3-20	2.2	2.2	1.3
<b>HTD-400</b>	2450	2050	800	2400	300	700	400	240	3-20	2.2	2.2	1.4
<b>HTD-500</b>	2650	2170	800	2400	350	700	500	250	3-15	3	2.2	1.5
<b>HTD-600</b>	2880	2300	800	2400	350	700	600	330	3-15	3	2.2	1.7
<b>HTD-800</b>	3030	2400	800	2800	400	800	800	400	3-15	4	2.2	1.9
<b>HTD-1000</b>	3120	2600	800	2800	400	800	1000	500	3-15	4	2.2	2