

Conveyor Elevator for Food C-type



C-type elevator is widely used in food, chemical, hardware and other industries. Suitable for conveying powdery, granular and small block of non-abrasive cut and small abrasive cut materials, currently used for weighing packaging machine feeding, color machine feeding and check feeding, automatic production line of three-dimensional cycle loading and unloading.

Features:

1. Large throughput, high lifting height.
2. Stable and reliable operation, long service life.
3. Closed environmental protection body: the whole machine shell is closed, reduce the dust flying caused by leakage during operation, to meet the requirements of environmental protection.
4. Feeding, conveying, unloading process, reduce the damage to the object itself, reduce reject rate.
5. Can be designed according to customer site, horizontal length ≤ 20 meters, vertical height ≤ 20 meters, to meet the use of different places.
6. Can be matched with vibration feeder, inflow type uniform speed feeding, reduce the phenomenon of overflow material leakage.
7. Save space, compact structure, small footprint.
8. Single point or multi-point automatic feeding, suitable for a row of multiple silo feeding.
9. The machine adopts flange connection, body and hopper using stainless steel material.
10. A variety of models: Z, C, suitable for different occasions.

Parameters:

Hopper capacity	4L
Material	304 stainless steel/ carbon steel
Transmission capacity	6-8M3/H
Voltage	AC220V/ 380V 50HZ/ 60HZ
Power	2.5KW - 4KW