

Automatic Powder Packaging Machine DXDF-40II/150II



Details:

I 、 Applications:

The machine is designed and manufactured specially for powdery and super fine powdery products Driven by servomotor, the auger is rotating to fill products; furthermore, the filling range can be adjusted automatically through computer The processes of bag making, measuring, filling, sealing, cutting, counting and hot pressing codes can be done automatically. Packing material include several kinds of heat-seal lamination, such as PET/plated AL/PE, PET/PE, NYLON etc.

II 、 Features:

1. All stainless steel cover meets to GMP standard.
2. Equipped with antipollution and dustproof device.
3. Automatic adjustment of pouch size and filling range.
4. Photocell controller is easy to manipulate.
5. Automatic self support lubricating system, the machine can work 24 hours
6. The operation facility is controlled by American intel computer, all function is displayed with digital screen.

7. Minimum sealing temperature variation employs PID temperature, the tolerance is controlled by $\pm 2\%$.
8. Along with assembling automatic no packing alarm system, help user to economize cost.
9. Equipped with easy open system.
10. Equipped long filling screw make the sealing area clean and strong and compact shut-off door is used to prevent from product clamping at sealing jaw.

III、 Option

1. Ink printer
2. Conveyor
3. Hot printing code

IV、 Technical Data

TYPE	DXDF-40II	DXDF-150II
Bag size	L55-110 /W30-80mm	L70-150 /W70-115mm
Capacity	50-110 bags/min	28-60 bags/min
Filling range	5-40 ml	30-150 ml
Power	220V, 50HZ, 1.5KW	220V, 50HZ, 1.9KW
Weight	350 KGS	450 KGS
Dimension (L*W*H)	600X 790X1780 mm	700X 800X1900 mm