

Automatic Shrink Packing Machine (Color Film) **BS-20/26**



Specification

Specification:

Voltage: 220V 50HZ

Power: 2KW

Max. packing size: 420 280 350mm L W H

Package speed: 17-25bags/min

Air source pressure: 0.5-0.7Mpa

Equipped with infrared ray hot air circle shrink tunnel

Power: 22KW

Conveyor speed: 0-15m/min

Shrink tunnel size: 2465 840 1700mm L W H

Note: the machines packing size and shrink tunnel is designed according customer requested speed and bottle size.

No	Model	BS-20	BS-26
1	Capacity	12000bph 500ml	15000bph 500ml
2	Gas requirement	0.4 ~ 0.6Mpa	
3	Working pressure	3PH 380V/50Hz, 42KW	
4	Air Pressure	0.6~0.8Mpa (without oil without water)	
5	Air consumption	80-100NL/min Pipe Joint Size: Φ10	
6	Shrink chamber L×W×H	1800×650×450(mm)	
7	Shrink temperature	200℃~280℃	
8	Packing Material	LDPE (dust & static electricity removed Width of film roll: ≤600mm Thickness of film: 0.06~0.10mm Diameter of film roll: ≤350mm Film reel diameter: 76mm	
9	Working noise	≤65dB	
10	Total weight	4000kg	
11	Environment condition	3-100 meters above sea level	
12	Environment temperature	5℃-40℃	
13	Environment Humidity	30-80 % without condensation	