

## *KL-320B/320D Rotary Pillow Packing Machine*



### **Main performance and structure features**

1. Dual frequency conversion control, Bag length can be set and cut in one step, saving time and film.
2. Interface features easy and quick setting and operation.
3. Self failure diagnosis, clear failure display.
4. High sensitivity photoelectric eye color tracing, numerical input of cutting/sealing position for extra accuracy.
5. Temperature independent PID control, more suitable for packaging different materials.
6. Positioned stop function, without sticking knife or wasting film.
7. Simple driving system, reliable working, convenient maintenance.
8. All control is realized through software, easy for function adjusting and technical upgrade.。

### **Application**

Packaging various kinds of regular objects like biscuits, pies, chocolates, bread, instant noodles, moon-cakes, drugs, daily appliances, industrial parts, paper boxes, plates, etc.

## Specification

Type	KL-320B	KL-320D
Film width	Max. 350mm	
Bag length	65-190 or 120-280mm	90-220 or 150-330mm
Bag width	50-160mm	
Product height	Max.45mm	Max.60mm
Film roll diameter	Max. 320mm	
Packaging rate	40-230 bag/min	
Power	220V, 50/60HZ, 2.6KVA	
Machine size	(L)3770X(W)720X(H)1450mm	
Machine quality	600kg	
Remarks	Optional Air filling device	