



## *Link-5570TBZ Automatic Heat Tunnel Shrink Wrap Packaging Machine*



Link – 5570TBZ type full automatic sealing and cutting machine, is widely used for packing product mass production line production, heat shrinkable film automatically send film punching, can automatically feed, transmission, covering film, sealing and cutting, and increasing heat shrinkable packaging machine one-time completed, the packing speed can reach 20-30 pieces per minute, high working efficiency, and can be adjusted according to the product specification only lead to membrane system And feeding platform, suitable for different heights and widths of product packaging, automatic sealing and cutting machine fast, convenient, can replace 5-7 manual, improve up to 80% of the production efficiency, is a good choice for enterprises to save costs, improve production efficiency, achieve packaging standardization.

### **Automatic sealing and cutting machine features:**

- Manufactured with international advanced technology and imported parts and electrical components, the whole body is thickened;
- Special steel sealing knife adopts Teflon coating to resist adhesion and high temperature, sealing will not crack, coking, smoke, zero pollution;
- Using constant temperature heating sealing and cutting system can be used to seal and cut POF and other industrial standard shrinkage film;
- Advanced PLC programmable controller, with stable protection and alarm device;
- The sealing and cutting part is equipped with plexiglass protective cover, with automatic alarm function, greatly improving the safety of the operator;
- Feeding length control Through the combination of electric eye detection and timer, accurately control the length of the film, so that the contraction effect is easier to control;
- Equipped with detection photoelectric, horizontal and vertical electric eyes two groups of electric eyes, easy to switch and select, for thin and small packaging, easy to complete sealing;
- Automatic coiling of waste materials, controlled by a separate motor, will not be too loose or too tight to crack, and waste materials are easy to disassemble;

- It is suitable for multi-item packing and pallet packing, and can also be used with automatic packing line;
- After sealing, cutting and heat shrinkage, the products are more beautiful, with moisture-proof, anti-corrosion, anti-impact and other functions;
- Tens of thousands of parts aging tests, to ensure that every detail is more stable, the failure rate is lower, can continue packaging production;

### Application scope:

Relying on the advantages of the above, this automatic sealing and cutting machine is widely used in printing, color box, greeting cards, photo albums, photo frames, medicine, electronics, daily chemicals, cosmetics, auto parts, hardware, food and other large-scale production of the industry.

### Technical Parameters:

Model	Link-5570TBZ
Installation dimensions	L 3000 * W 1400 * H 1540 mm
Maximum sealing size	L 700mm
Maximum packing size	L unlimited * W 580 * H 300; W+H≤650mm
Furnace chamber size	
Packing speed	15-25 PCS/min
The net weight	600kg
Power	2.7kw
The power supply	3Φ380V 50/60Hz
Applicable air	5.5kg/cm <sup>2</sup>