

SHL-2586

Horizontal Labeling Machine



Features:

- This labeling machine is suitable for Ampoule, Oral liquid bottle and the slightness bottles.
- Double transporting tracks. Upper one is for labeling the bottles and the lower is for transporting bottle pallets. So that the labeled bottles will fall in to the pallet allurately.
- Auger applies in bottles separation mechanism, ensure the distance between the bottles correct.
- Bottles upright transporting horizontally, steady and easy operate.
- Labels orientation device make the labels' position error less than $\pm 0.5\text{mm}$.
- After labeling, the failure rate is less than one ten thousandth.
- Function of alarming when lack of labels.
- Panasonic servo motor adopted in the machine's main motor, PLC controlled with touch screen. Fast speed and steady performance.
- This machine designed elaborately, compact structure, steady performance, convenient debugging. Suitable for various specs bottles' labeling and enter into pallet.

Technical Parameter	SHL-2586
Electric Voltage	AC220V 50/60HZ
Power	1.5KW
Labeling Spees	0-400BMP(depend on the length of label)
Labeling Precision	$\pm 0.5\text{mm}$
Lettering machine speed	0-400(synchronize with labeling)
Container's range	Length 25-120, Diam 10-30
Label's range	Height 20-90mm,Length 25-100mm
Max. label roll	Diam 420mm,Inside diam 76mm
Overall dimensions	3600×1800×1700(L×W×H)