

DXDL140IIE_PLC Intelligence Packaging Machine



The process of measuring, bag-making, filling, sealing, printing and cutting can be done automatically.

The packaging machine can pack many kinds of material such as grain, powder, liquid and tablet, etc.

Purpose:

Liquid and sauce kind: Syrup, honey, jam, ketchup, shampoo, liquid pesticide, etc.

Technical Features:

- 1. Adopts the man-machine conversation interface, PLC and the transducer communicating with each other to display and control the each functions and the running state. Stable and reliably.
- 2. The Double channel temperature of the horizontal and vertical is controlled by intelligent temperature controlling device.
- 3. Intelligent photo cell orientation, transform discretionarily between the light/shade. Strongly antijamming, when two bags can't catch up with the upper mark the machine will stop and give an alarm.
- 4. The packaging speed can be adjusted continuously within specified range. Orientation open mouth and stop.
- 5. The integrative cutter has a device of dustproof with it. It is very easy to adjust the cutter's position.
- 6. The bag-making has high precision. Easily Operation and maintain.
- 7. Having functions just like paper cutting, bag-stopped up, safe door detecting and so on.
- 8. Measurement adopts adjustable cup method, which is accorded with the national measurement standard.

Technical Parameter:

• Power: AC 380V / 50HZ three-phase five-wire system

Pouch length: (L)50~205 mm
Pouch width: (W)40~140 mm
Packaging speed: 28~50 Bag/min

• Filling Capacity: 1~100 ml

• Seal Style: Pillow

Power Consumption: 1.65 KwMeasuring Method: Piston Pump

• Weight: 270 Kg

• Dimension: 995 mm (L) x 800 mm (W) x 1975 mm (H)