



## *MIC-DT60 Automatic Front&back Sides Labeling Machine*



Control system: SIEMENS PLC control system, with stable operation and extremely low failure rate;

Operation system: SIEMENS touch screen, directly visual interface and easy operation, Chinese and English language change conveniently, also with help function and fault display function;

Check system: Use German LEUZE check label sensor, automatic check labeling station, stable and convenient don't have much higher requirement with worker;

Send label system: use SIEMENS high-power servo control system, stable and high speed ;

Parameter SAVE: can save 30 groups labeling parameters, when change bottles, don't need reset parameters, just adjust the machine part is ok.

Alarm function: label spill, label broken or other malfunction during working, machine will alarm and stop working.

Machine Material: Whole machine and spare parts use material S304 stainless steel and anodized senior aluminum alloy, with high corrosion resistance and never rust;

## Technical parameter

Model	MIC-DT60
Driving Mode	Servo motor
Yield (pcs/min)	20-180( depends on bottle and label sizes )
Operating direction	Left or Right
Conveyor Speed (m/min)	≤40
Labeling Accuracy	±1.0 mm
Label roll inner diameter	76 mm
Label roll outer diameter	350 mm(max)
The suitable size of label	Standard size: H: 15-180 mm L: 15-300 mm
	(Other size can customized )
The suitable size of bottles	Can customized
Printer device use air	5kg/cm 2
Power (w)	1000W
Weight (kg)	350
Conveyor height	950±50mm (Height can customized)
Machine size	3000 (L) 1800 (W) 1800 (H) mm
Voltage (In China)	AC220V 50/60HZ Single phase
	(Can customized )