

## ***CHS-6605 Automatic Top Flap Folding Carton Sealer / Top & Side Belt Drive***



### **Features**

- Carton dragging by Top & Side belts with independent motors
- Crank handle adjustment of carton width and height, easy operation and no need professional technicians
- Pneumatic flap folding. To closes all top flaps and seals the top & bottom of carton
- Carton sealer is designed with a stable four-column support structure
- Suitable for big and heavy boxes especially
- Can bear up to 35kg loading
- Stainless roller table for carton movement
- Carton sealing: top and bottom
- Two sides compression rollers, have better tightness
- The tape head is developed and produce by CHA PACK, the length of tape that can be placed up to 900m. (260mm diameter)
- Dual telescoping mast with cushion. Adjust the unevenness of the carton.
- Machine with mobile locking casters, easy to move anywhere
- Emergency stop on top taping head for quick access
- Parts are manufactured with mold.- Stable quality, Short lead time
- Carton sealer is designed to meet the needs of uniform in-line carton closure applications
- Machine can be available with other equipments, e.g: 1. Labeling mc. 2. Weighing mc. 3. Inkjet Printers
- Machines are designed and produced by ourselves. Rugged design, low maintenance rate
- 90% self-production rate, 100% Made in Taiwan.

## Specification

Model	CHS-6605
Function	Top & Side belt driven
Power Supply	1 phase, 110V/220V/240V
Tape Width	2" or 3"
2" & 3" Tape Sealing size	L250-500mm, W155-500mm, H120-500mm
Tape overlap	L60±5 (mm) standard
Working table height	570-770mm
Conveyor Speed	20 M/min
Capacity	9~10 cases/per min. ( Data is for carton length=300mm)
	*** Depending on box size and operator efficiency.***
Control system	Traditional distribution
Machine dimension	L1960 x W930 x H1560mm
Air compressor	6kg/cm <sup>2</sup>