

Octagonal Blender



SALIENT FEATURES

- Contact parts in stainless steel 304 or 316.
- Octagonal shaped with rectangular center, conical discharge frustum and rectangular top frustum.
- Baffles provided in the shell.
- Manhole with gasket is provided to fix baffles and for ease of cleaning the shell.
- Charging and discharging is through a butterfly valve. A conical adaptor can be provided for fixing charging
- Drum after butterfly valve.
- Unit can be provided with bin charging arrangement.
- All moving parts are enclosed in guards.
- A safety railing with a limit switch is provided for operator safety.
- Manual Inching arrangement can be provided.
- Flame - proof motors with flame - proof push button stations can be provided.

TECHNICAL SPECIFICATIONS

MODEL	GROSS VOLUME	WORKING VOLUME	MOTOR	OUTPUT SPEED	DISCHARGE VALVE	OVERALL DIMENSIONS		
	litres	litres	hp	rpm	inches	mm		
						WIDTH	DEPTH	HEIGHT
OB 5	12	10	0.5	12	4"	600	350	600
OB 10	25	20	0.5	12	4"	700	400	800
OB 25	50	40	0.5	12	4"	900	1200	1400
OB 50	125	100	0.5	8	6"	1100	2000	2200
OB 100	250	200	1	8	6"	1200	2200	2500

OB 150	375	300	1	5/10	6"	1400	2200	2500
OB 200	500	400	1.5	5/10	6"	1400	2400	2600
OB 250	625	500	2	5/10	8"	1500	2600	2600
OB 500	1250	1000	3	5/10	10"	1800	2800	2900
OB 1000	2500	2000	5	5/10	12"	2000	3000	3200