

XT-FTB 11300 Automatic Flat Labeling Machine



1. Wide applicable range. It is applicable to flat labeling and adhesive sticker film for products with a width of $30 \text{mm} \sim 350 \text{mm}$. Uneven surface labeling can be realized by replacing of marking machine.

2. High labeling precision, the unique design can ensure no offset will occur during label drawing process.

3. Sturdy and durable. Three rod adjustment mechanism is to be adjusted. The complete machine will be solid and durable.

4. High stability. The electronic control system adopts products of international or domestic well-known brands.

5. Simple adjustment. 6-degree of freedom is designed for adjustable seat. Conversion between different products will become simple and time-saving.

Product Details:

1. Applicable labeling length: 6mm~250mm, applicable labeling width (width of backing paper): 20mm~150mm

2. Applicable product dimensions (L*W*H/Thickness): L: 40mm~400mm, W:

40mm~200mm,Height: 0.2mm~150mm

3. Applicable roll OD (mm): below φ350

Applicable roll ID (mm): φ76mm

- 4. Labeling precision (mm): ±1mm
- 5. Packaging speed (pcs/min): 30 -60 pcs/min.
- 6. Weight (kg): about 180kg
- 7. Frequency (HZ): 50 HZ; Voltage (V): 220V; Power (W): 420W
- 8. Equipment overall dimensions (mm) (L*W*H): 1600mm*780mm*1400mm