

LQ-XKS-2 Automatic Sleeve Shrink Wrapping Machine

Automatic sleeve sealing machine with shrink tunnel is suitable for shrink packaging of the beverage, beer, mineral water, pop-top cans and glass bottles etc without tray. Automatic sleeve sealing machine with shrink tunnel is designed for packing single product or combined products without tray. the equipment can be connected with the production line to complete feeding, film wrapping, sealing & cutting, shrinking and cooling automatically. There are various packing modes available. For combined object, the bottle quantity can be 6, 9, 12, 15, 18, 20 or 24 etc.

Feature

Shrink machine:

- 1. Designed based on advanced technology and artwork introduced from abroad to ensure stability and reliability of equipment.
- 2. The conveying belt can be set for left feed-in or right feed-in as required.
- 3. The machine can pack 2, 3 or 4 rows of bottles with or without tray. Only need to turn the switchover switch on the panel when you wants to change the packing mode.
- 4. Adopt the worm gear reducer, which ensures the stable conveying and film feeding

Shrink tunnel:

- 1. Adopt double blowing motors for BS-6040L to guarantee even heat inside the tunnel, which leads to good appearance of package after shrinking.
- 2. The adjustable hot air guide flow frame inside the tunnel makes it more energy saving.
- 3. Adopt solid steel roller covered with silicone gel pipe, chain conveying, and durable silicone gel.

Technical Parameter

Power supply	AC 380V/50Hz	
Compressed air	60Lt/min	
Power	18.5kw	
Max. package size	450mm*320mm*200mm	
Max.film width	600mm	
Packaging speed	8-10pcs/min	
Cutting length	650mm	
Cutting time range	1.5-3s	
Temperature range	150-250°C	
Film thickness	40-80μm	
Shrink tunnel size	1500mm×600mm×250mm	
Machine size	3600mm×860mm×2000mm	
Weight	520kg	