

ZTV-N2 Small Bag Automatic Vacuum Packaging Machine Unit



The functions of ZTV-N2 include automatic feeding, weighing, vacuum packaging, sealing, and printing, counting, punching and finished product conveying. It adopts PLC control apparatuses which are imported from well-known international companies. Thus, they are of reliable performance. The finished products done by automatic vacuum packing machine are of magnificent appearances.



Main performance and functional characteristics:

1. Equipped with safety protection, comply with firm's safety management requires;

2. Use intelligent temperature controlling machine to have accurate temperature control; ensure the artistic and neat seal;

3. Use PLC Servo System and pneumatic control system and super touch screen to form the drive control center; maximize the whole machine's control precision, reliability and intelligent zed level;

4. Touch screen can store the technical parameters of various kinds of products, no need to reset while products changing;

- 5. Have error indicating system, helping to handle the trouble immediately;
- 6. Make block bags and hanging bags according to customers' different requires;
- 7. Both stainless steel machines and carbon steel machines;
- 8. Single-belt transportation, placidly and quickly, small friction, little waste;
- 9. Have stainless steel model and carbon steel model for choose.

Technical parameters:

Model	ZTV-N2
Measuring range	15-25g
Measurement accuracy	±0.5g
Bag Type	4sides sealing bags in chain
Operation Mode	Intermittent
Speed	Up to 40 bags/min
Bag Length	50-200 mm
Bag Width	50-130 mm
Reel Film Width	280 mm
Film Thickness	0.04-0.12 mm
Reel Outer Dia	Ф350 mm
Reel Inner Dia	Φ75 mm
Voltage	AC 220V/ 50HZ, 1phase or per customer needs
Power Consumption	5KW
Compressed Air Requirement	0.6MPa, 0.36 M3 / Min
Weight	1300KG
Dimension	2700x1000x1800mm(LxKxH)