



Automatic Granule Packaging Machine DXDK-40II/150II



Details:

I 、 Applications:

The machine is suitable for packing non sticky, bulk or granular material, such as medical pills, food Stuffs, plant seeds, washing powder, coffee, sugar, desiccant etc The integrated processes of bag making, measuring filling, sealing cutting, counting and hot pressing codes can be done automatically. Packing material include several kinds of heat seal lamination, such as PET/plated AL/PE, PET/PE, PAPER/PE,NYLON etc.

II 、 Features:

1. All stainless steel cover meets to GMP standard.
2. Equipped with antipollution and dustproof device.
3. Automatic adjustment of pouch size and filling range.
4. Photocell controller is easy to manipulate.
5. Automatic self support lubricating system, the machine can work 24 hours and the maximal capacity is 110 bags/min.
6. The operation facility is controlled by American intel computer, all function is displayed with digital screen.
7. Minimum sealing temperature variation employs PID temperature, the tolerance is controlled by $\pm 2\%$.
8. Along with assembling automatic no packing alarm system, help user to economize cost.
9. Equipped with easy open system.

III、 Option

1. Ink printer
2. Conveyor
3. Hot pressing codes

IV、 Technical Data

TYPE	DXDK-40II	DXDK-150II
Bag size	L55-110 /W30-80mm	L70-150 /W70-115mm
Capacity	50-110 bags/min	35-60 bags/min
Filling range	5-40 ml	30-150 ml
Power	220V, 50HZ, 1.5KW	220V, 50HZ, 1.5KW
Weight	350 KGS	350 KGS
Dimension (L*W*H)	600X 790X1780 mm	700X 800X1900 mm