

100B/H 5GL Filling Machine



Model: XG-100/J(100B/H)

PLC Controlled Washing Filling Capping Machine 100B/H

General Power: 2.0Kw 220V 50HZ

Bottle Spec: 270*490*56 (5Gallon) or 213*415*56 (3Gallon)

Working Pressure: 0.5Mpa

Washing Filling Rate: 100B/H

Outer Size: 2940*700*1550

Packing Size: 3190*950*1800

G/N.W: 318/216Kgs

PLC (From Japan or Taiwan) control /Stainless steel frame.

Famous electronic components such as Merlin Gerlin, Turck and so on

Features:

1. Automatic protection for power leakage and short circuit
2. Low-pressure protection: when incoming air's pressure is $\leq 0.5\text{MPa}$, the equipment will be automatically stopped
3. Water-shortage protection: when the level of the water tank is lower than the liquid switch, the equipment will be automatically stopped
4. Low water level protection for finished water tank (water tank with filler's water supply): when the water level of the tank is lower than that of the liquid switch, the equipment will be automatically stopped
5. Special filling principle-dual filling (at the early filling stage, the two filling valves work simultaneously; after some time, the auxiliary filling valve stops working, while main filling valve keeps working) avoid water to be waste
6. Filling time adjusted between two levels: 0.1S and 1S, ensuring the precision for filling amount.