



Horizontal Food Pouch Packing Machine DK-260 B/D/E/S



Horizontal food pouch packing machine is suitable for packaging of various regular objects such as food, hardware, toys, medicines, industrial supplies and daily necessities.

Main performance and structural characteristics

1. Double frequency converter control, the bag length can be set and cut, no need to adjust the air, one step in place, saving time and film.
2. Man-machine interface, parameter setting is convenient and quick.
3. Fault self-diagnosis function, the fault display is clear at a glance.
4. High-sensitivity photoelectric eye color mark positioning, digital input sealing and cutting position, making the sealing and cutting position more accurate.
5. Temperature independent PID control, better suited to a variety of packaging materials.
6. Positioning stop function, no sticking knife, no waste film.
7. The transmission system is simple, the work is more reliable, and the maintenance is more convenient.
8. All control is realized by software, which is convenient for function adjustment and technology upgrade, and never lags behind

Technical Parameters:

| Model | DK-260B | DK-260D | DK-260E | DK-260S |
|----------------|--------------------------------|----------------|----------------|----------------|
| Film width | Max.260mm | | Max.180mm | |
| Bag length | 65-190or120-280mm | 90-230mm | 50-115mm | 45-90mm |
| Bag width | 30-110mm | | 30-80mm | |
| Product height | Max.40mm | Max.55mm | Max.35mm | |
| Film dia | Max.260mm | | | |
| Packing speed | 40-250bag/min | | 60-330bag/min | |
| voltage | 220V 50/60Hz 2.4kw | | | |
| Machine size | (L)3770X(W)670X(H)1450mm | | | |
| Machine weight | About 700kg | | | |
| Note | Other demand can be customized | | | |