



## ***CHIC-VM1N30 Automatic Granule Grain Packaging Machine***



Linear weigher is suitable for weighing slice, roll or regular shape products such as sugar, salt, seed, rice, sesame, glutamate, milk powder, coffee powder and seasoning powder, etc.

### **Main Features:**

- \* High precision digital load cell (HBM load cell is optional)
- \* Color touch screen (Mouse, SD card and memory card are compatible)
- \* Multilanguage choice (Translation is needed for some specific language)
- \* Different authority management

### **Special Features:**

- \* Self-diagnose function on the electronic boards
- \* Parameters can be freely adjusted during running condition

### **Technical characteristics:**

1. Easy to operate, adopt advanced PLC from Japan Mitsubishi, mate with touch screen and electric control system, the man-machine interface is friendly.
2. Automatic checking: no pouch or pouch open error, no fill, no seal. the bag can be used again, avoid wasting packing materials and raw materials.
3. Safety device: Machine stop at abnormal air pressure, heater disconnection alarm
4. The width of the bags could be adjusted by electrical motor.
5. It matches with the glass safety door. The machine will stop working when you open the door. So that it could protect the safety of operators. At the same time, it could prevent dust.

6. The packing materials loss low, what this machine is used the preformed bag, the bag pattern is perfect and has a high quality of the sealing part, this improved the product specification
7. With different feeders changed to pack solid, liquid, thick liquid, powder and so on
8. The packing bag suits in extensive range, suit for multi-layer compound, monolayer PE, PP and so on Preformed bag made by film and paper.

**Technical information:**

<b>Model</b>	<b>CHIC-VM1N30</b>
Range of SNGL bag WGT	20-2000g
AV SNGL bag ERR / Weighing Accuracy	0.2-2g
Max weighing speed	5-20/min
Hopper volume	3L
Control system	MCU
Preset Programs	10
Max. Mix-Products	1
Operation Panel	7 inch touch screen
Voltage/Power/Frequency/Rating Current	AC220V ±10% 50Hz(60Hz)
Packing Dimension (mm)	1010(L)*960(W)*1207(H)
Packing Weight	250KG