

DHP-250P Blister Packing Machine



The machine feeder can be connected with labeling machine and output can be used with cartoning machine, thus forming a complete automatic packaging production line. Equipped with PLC and HMI touchscreen control system. Uses servo motor-driven and the main motor adopts frequency control. With special automatic servo drive feeder for ampoule, vial and pre-filled syringe. This machine is equipped with blister forming detection, feeding detect rejection, safety cover, and chiller cooling system.

Application:

It is suitable for ampoule, vials and pre-filled syringe etc.

Technical parameters:

| | |
|-------------------------------|--|
| Cutting Frequency (times/min) | 25 |
| Max. Forming Area (mm) | 245 x 130 x 35 |
| Packaging Material (mm) | PVC : 260 x 0.25 (0.15-0.5) PTP : 260 x 0.02 |
| Stroke | Kurang dari atau sama dengan 130 mm (according to customers request) |
| Electromagnetic Valve | SMC (Japan) |
| Pressure sensor | To detect minimum air pressure |
| Transducer | Omron (Japan) |
| Production Capacity (pcs/h) | Max. 6000 (The specific output should be considered according to blister and ampoule size) |
| Air Pressure (Mpa) | 0.6-0.7 |
| Air Supply (m3/min) | lebih dari atau sama dengan 0.38 (self-prepared) |
| Power Supply | 380 V / 50 Hz |
| Total Power (Kw) | 6 |
| Temperature Control | To control temperature |
| Overall dimension (LxWxH) mm | 4200x1400x1700 |