

Automatic Dry Fruit Packaging Machine ZP-3000S



The automatic dry fruits packaging machine ZP-3000S adopts industry-leading electronic cam algorithm, and the bag lengths range from 90mm – infinite. Once the bag length is determined, it can be cut in one step, saving time and film.

Features of Automatic Dry Fruit Packaging Machine ZP-3000s

- 1. The plastic film packaging equipment detects and sets the bag length automatically.
- 2. The automatic dry fruit packaging machine is easy to maintain or change location, ensuring long life and hygiene.
- 3. Digital screen and transducer control the automatic dry fruit packaging machine to ensure easy operation.
- 4. Double transducer control with stepless speed shift and wide adjustment, can be perfectly matched with the previous process of the production line.
- 5. With menu storage and memory functions, the controller can save multiple sets of parameter configurations, and when the product or packaging film is changed, the formula can be used through the touch screen.
- 6. Advanced electronic anti-cutting, electronic anti-aircraft bag algorithm. The feed detection electric eye will automatically position the product, and the empty material film will stop, saving packaging materials.
- 7. Man-machine interface, convenient and quick parameter setting, automatic tracking of color code, automatic correction of cutting length. Digitally input the sealing and cutting position to make the sealing and cutting position more accurate.
- 8. The fault is automatically diagnosed, and the fault display is clear at a glance.
- 9. The standard horizontal sealing cutter shaft center distance is 132 double cutters, and the cutter distance can be changed to 114 or 90. According to the actual size of the product, when the product is small and the required packaging speed is high, the cutter distance of 114 or 90 can be selected.

Technical Parameters

Machine Model	Automatic Dry Fruit Packaging Machine ZP-3000s
Packing speed	35-80 bags/min
Packing material	Plastic film (OPP/CPP、PT/PE、KOP/CPP、ALU-FOIL)
Bag style	Pillow type/fat pouch (3-side presealed)
Bag size (L*W*H)	90- unlimited,35-140mm,5-50mm
Film width	90-360mm
Packing Dimension (L*W*H)	4000mm*950mm*1600mm
Heat power	3.8kw
Motor power	2.5kw
Total power	6.3 kw
Overall weight	630kg