



ZHSP-100Y Sleeve Inserting Machine



Multi Pack supplies automatic customized secondary packaging machinery for food products, beverages, liquid chemicals, pharmaceutical products and cosmetics, toiletries, lube & edible oil, pesticides & ancillaries etc

Synchronous transmission system with a strap, changing any strap can finish in 3 min. it maintains more easily and simply, and it does not affect to manufacture.

- It is suitable for the containers of $\phi 30-120\text{mm}$. The cutting seat need not change and debug, and has priority over congeneric productions. The new reamer cuts smoothly and constringency more beautiful.
- Steam shrinkage furnace, safe, easy, efficient! High energy sources efficient: it can finish shrinkage perfectly with lowest energy sources.
- Safety design: special Thermal insulation layer design, furnace outside keeps normal temperature, doesn't hurt operator at all. special door clamp design, keep energy sources inside and airproof.
- Originate automatic mechanism of incepting label (option) reduces labor intensity consumedly.
- With particular design of transmission mechanism, cutting seat and reamer, it shows disdain for the same trade.
- With servomotor, high speed, excellent stability.
- With high-tech microcomputer controlling, the rate of trouble is low, and servicing is speedy.

Techno-parameter:

Main machine:

- Speed:100bpm
- Power supply:φ AC220V 50/60hz
- Power consumption: 3KW
- Outside size:2400(L)*9500(W)*2500(H)
- Quantity of air consumed:50kg/hr
- ContainerRange: 30—85mm (Dia.)
- LabelRange:40—240mm (L)
- 0.035—0.082mm (Thickness)

Steam shrinkage furnace:

- Power supply:φ AC220V 50/60hz
- Power consumption: 0.75KW
- Outside size:2000(L)*400(W)*2100(H)