



High Speed Automatic Flow Packing Machine Cereal Protein Bar Pillow Packaging Machine JY-L1000



The fully automatic pillow packing line is suitable for pillow packing of fragile surface and easily damaged items, such as chocolate, wafer, puff, cake, Swiss roll, nougat, crisp sugar, pine tower, cotton candy and other candies and their coated products. It can achieve full automation from the output port of product molding equipment through docking conveying, shunt, finishing and packaging, and can be customized to meet the output of supporting molding equipment through various ways.

Major Parameters of the Equipment

- * Packing speed : 50-1000 bags/min (The packaging speed is determined by the product size and packaging film material)
- * Finished Bag Size : 15-200*15-60*5-30mm
- * Voltage : 380V; 50HZ, 3phase (Can be customized)
- * Total Power : 9.5KW
- * Dimensions : 8900mm*1180mm*1786mm
- * Net Weight : 3500KGS

Performance Characteristics

- * Stainless steel 304 machine frame.
- * Can be connected directly with production line, make products sending, forming, filling and sealing with fully automatic.
- * Full automatic, Photoelectric sensor tracking system, no empty package.
- * Multiply Servo motor configuration (Nine servo motor) simply construction, easy maintenance.
- * With automatic film roll link, Reduce packaging waste and improve work efficiency.
- * High speed, Durable structure.
- * Stainless steel body frame, all belt with food grade PU

Technical Parameter

Scope of packaging film	Knife count	Packaging speed (bags/minute)
90-180mm	2	200 bags/minute
65-120mm	3	400 bags/minute
55-80mm	4	600 bags/minute
48-60mm	5	800 bags/minute
45-55mm	6	1000 bags/minute