

KD-350 Automatic Horizontal Flow Pillow-Type Packing Machine



Suitable for biscuits, packaging of all kinds of objects with regular solid state, such, as bread, speed wheaten food, moon, cake, candy, medicines, daily necessities, five metals part, paper carton or the tray, etc

Features:

1. Compact structure, stable function and simple operation.
2. Double frequency converter controller, length of package will cut immediately once setting, adjustment needless, saving time and film.
3. It adopts imported electric appliance, touch man machine interface, convenient parameter setting.
4. Self-checking function, trouble can be read easily. High sensor photoelectric color chart tracking, make the cutting position more correctly.
5. Dependent temperature PID controlling suitable for various materials of packaging membrane. Position stop function, no adhesive and no waste of membrane.
6. Clean rotation system, more reliable operation and more convenient maintenance.
7. All the controlling operates by the software, convenience for function adjustment and technical up grading.

Technical parameters:

Max.film width	350mm
Max packaging capacity(according to its material to fix)	40-220 times/min
Suitable film thickness	0.03-0.06mm
Length of bags	65-330mm
Packaging width	30-150mm
Packaging height	≤50mm
Total power	3.2Kw 220V
Overall dimensions (L * W * H)	4100*1050*1560mm
Weight	600KG