

QSJ5040A Sleeve wrapper packaging machine



QSJ-5040A is suitable for wrapping products such as pop-cans and bottles, etc, it works with PE shrink tunnels.

Characteristic:

The Machine adopts the advanced touch screen system for man-machine conversation, 'Omron' programmable logic controller (PLC), 'AirTAC' air-jar, and all the rest parts adopt international famous brand.

Up and down magnetic switch prevent sealing mistakes, and protect the operators.

Intelligent temperature controller performs stable.

Large power conveyer motor, with stepless speed regulating, ensures smooth feeding.

Up and down large power fan system ensures the excellent effect of shrinking in one time.

Super cooling system cools the packing and makes the figuration perfectly.

Specification

Model	QSJ-5040A	Model	BSE5040A
Voltage	3phase 220V/380V, 50-60HZ	Power supply	3phase 220V/380-460V 50-60HZ
Power	3KW	Heater power	20KW Adjuster
Capacity	0 - 10pcs/minute	Conveyer speed	0-10m/minute
Working air pressure	0.4-0.6Mpa	Tunnel size(L*W*H)	1500*500*460mm
Width/thickness of the film	Max. 590mm/0.03 - 0.25mm	Conveyer loading	30KGS MAX.
Max. packing dimension(L*W*H)	450*300*350mm	Machine size(L*W*H)	2500*820*1680mm
Min. packing dimension(L*W*H)	250*50*100mm	Machine weight	470KGS
Machine size(L*W*H)	1,060*1,600*1,930mm	Shrink film	PE,POF,PVC,PP
Machine weight	370kg		