



ZP35A

Rotary Tablet Press Machine

Application:

This machine is a double-press type continuous automatic tablet press for pressing granular raw materials into tablets. It is mainly used in pharmaceutical industry and also the chemical, food, electronic industries.

Characteristics:

- Produce all kinds of round tablets and irregular tablets.
- The outside part of the machine is fully-enclosed, the material of the cover and the inside table face is stainless steel. The turret face is specially disposed keeping the luster of the face and prevent the cross pollution, meeting the G.M.P requirement.
- It has transparent windows so that press condition can be observed clearly and the windows can be opened. Cleaning and maintenance is easier.
- The lay-out of all the controllers and the operate parts is reasonable.
- The speed adjustment of the driver is controlled by the frequency conversion device.
- All the drive devices are located inside the machine so keep the machine clean.
- The hydraulic system can assure the stable of the system.
- An overload protection unit is included in the system to avoid the damage of the punches and apparatus, when overload occurs, the machine stops automatically.
- This machine also has electronic magic driver and other safety protection device which can be adjusted and operated when running.
- The punches and dies are also applicable to Model ZP19, ZP33, ZP33B, ZP35 and ZP37.

Main Technical Specifications					
Model	Unit	GZPK1042 GZPK1042A	GZPK1038 GZPK1038A	GZPK1032 GZPK1032A	GZPK1026 GZPK1026A
Number of Stations	set	42	38	32	26
Type of P/I		IPT19(EU19)BBS	IPT19(EU19)BB	IPT19(EU19)B	IPT1"(EU1)"D
Max main pressure	KN	100			
Max pre pressure	KN	20			
Max. Diameter of Tablet	mm	11	13	16	25
Max. Depth of Fill	mm	18			
Max. Capacity	Pc/h	252000	228000	192000	117000
Motor	KW	7.5			
Height with feed hopper	mm	2050			
Cover space	mm	1100*1100			
Weight	kg	3000			