

TY-702-120 Automatic L-Sealer



TAYI YEH TY-702-120 Auto L-Sealer offers quality packaging solution for larger packages. Operator-friendly and easy adjustment enable it widely uses in the factories.

Features

- Safety protection & alarm
- Integrated seal knife with curved joint for smart sealing line recondition
- Heavy duty sealing knives, no build-up & smoke whilst sealing
- Isolated perforating rod for easy adjustment without tearing line
- Easy operation & adjustment
- High efficiency to maximize capacity
- Extra pin roller guide for better film control and saving
- PLC control system alternative in standard program and timer control
- Temperature, Sealing Time, Sealing Height adjustable
- Suitable for POF & PE film

Specification

- Production capacity*: up to 20 packs per minute
- Conveyor speed: 26 meters per minute (constant speed)
- Electrical: 220 Volt, mono phase, 14 Amps, 3.0 KW
- Compressed Air requirement: 70PSI
- Machine Dimensions: 2560(L) x 1130(W) x 1580(H) mm
- Package Range: 120-700(L) x 200-500(W) x 5-120(H) mm

Sealing length (End): 750 mm
Sealing length (Side): 840 mm
Maximum product height: 120 mm

• Elevation: 750 mm

Applications

Widely adopted by general industries such as food, canned food, electronics products, toys, salted materials, metal wares, tools, cosmetics, pharmaceutical, daily essentials for shrink wrap purpose.

^{*} Production capacity is subject to product size, type of product, shrink film material and shrink film thickness.

^{**} Specifications are subject to change without prior notice.