



CFGNYZ-80A-C TUBE FILLER (applicable to plastic tubes, laminated tubes and metal tubes)



Parameters:

Adapt to the maximum tube diameter:

Metal tube: 10-35 mm Plastic tube and laminated tube : 10-60 mm

The maximum volume:

Metal tube:1-150 ml Plastic tube and laminated tube : 1-250 ml

Produce speed : 30-80 pcs/min

Air pressure : 0.4-0.6 Mpa

The power of machine : 2.2kw


Filling precision : $\leq \pm 1\%$

Features:

- The tube is automatically pressed into the tube holder.
- The elastic tension type tube holder is adopted to guarantee the consistent sealing height.
- The automatic color mark adjusting systems by stepping driving tube holder is adopted for oval tubes or other special-shaped tubes.
- Adopt mechanical transmission mode filling system ensuring the stability of loading capacity.
- Original Swiss LEISTER heater is adopted .
- The internal wall of tube adopts hot air sealing and the external wall of tube adopts cooling water circulative cooling, which can beautiful sealing effect.
- The fan (made in Taiwan) is adopted to discharge the poisonous gas produced during the heating outside the room.
- After the sealing, the wind cooling system is adopted to prevent the heat from being conducted to the ointment.
- PLC automatic control system.
- Highly clearl stainless steel frame.
- The connection of emulsifier 、 cartoning machine and filling machine can be easily achieved.
- It is easy to operate between different sizes of tubes.
- Automatic completion of filling 、 sealing and batch No. printing in one machine.
- Provided such functions as automatic supply of a tube to a worktable of machine、 automatic tube blowing(clearing)、 tube color mark automatic adjustment in a holder and automatic filling and sealing.
- Speed shall be adjustable by inverter.
- The production capacity can be realized and control automatically.
- The code mechanical hand print the code automatically in the request position.
- Human-machine interface with direct display and control.
- Tube feeding、 absorbing and locating device, which is controlled by the original FESTO vacuum generator.
- Automatic detection of tube direction inversion., Omron inversion detection phototube can accurately detect the inverted tube.
- Cam indexing.
- Automatic cleaning the inner tubes and the dust collecting system.
- Provided with malfunction alarm, automatic stopping device when the door is opened and mechanical overload.
- The combined material feeding forms of blow cutting and cutting can guarantee the filling of high viscosity.
- Column stylel material temperature automatic control blending system. **(optional)**.
- Ultrasonic hopper level sensor. **(optional)**

USA BANNER ultrasonic level probe combined with Siemens module can be used to accurately control material level and give direct display on the touch screen

- No tube no fill.
- Material pump. **(optional)**
- Water cooler(chiller). **(optional)**



YANTAI CHAOYUE MACHINERY EQUIPMENT CO.,LTD.

烟台超越机械设备有限公司

地址: 烟台市芝罘区幸福中路216-2号

Add: Room 2 No 216 Mid Xingfu Rd Zhifu District, Yantai China

电话(Tel): 0535-6819538 6804585

手机(The Mobile): 13854578998

传真(Fax): 0535-6819538

邮编(Post): 264002

公司主页(Website): www.ytcym.com

电子信箱(E-mai): leader_ytcym@126.com



www.ytcym.com