



SS-530/800/930/1100



Automatic Side Sealing Machine

The Advantage machinery Side Sealer Series is great machine for high speed packaging applications. The machine is controlled via a touch screen control which allows the operator to set the different times for the sealing operation, the temperature of the blades and also the length of film that is to be used. The machine has a variable conveyor speed controller which makes the machine ideal for both manual and automatic feeding. The machine is very efficient and user friendly.

- Some of its features are:**
- Touch Screen Control.
 - Quick change over between productions and sizes.
 - Horizontal and Vertical sensors for the packaging of different products.
 - Solid knife sealing blade makes a consistent seal and is long lasting.
 - Intermittent Sealing Motion (Side Seal) allows for infinite product lengths.
 - Automatic film advance allows for light weight products to easily be fed through.
 - Automatic waste removal system.
 - Can use with existing tunnels or you can choose from our wide selection.



Model	SS-530	SS-800	SS-950	SS-1100
Product Size LxWxH (in)	(3.15~∞)x(1.9~16.54)x(0.20~7.87)	(3.9~∞)x(3.15~23.6)x(0.08~5.91)	(7.87~∞)x(5.91~32.2)x(0.39~7.09)	(11.8~∞)x(7.87~39.3)x(0.39~7.09)
Sealing Blade Size (in)	20.87	33.07	37.40	44.88
Max. Speed (Pieces/min)	60	40	40	30
Max. Film Width (in)	25.5	41.73	44.49	53.15
Conveyor Speed(ft/ min)	0.03 - 0.10	0.03 - 0.10	0.03 - 0.10	0.03 - 0.10
Power (Volt./ Ph./ Amps/ Kw)	220 / 1 / 15 / 3	220 / 1 / 23 / 4.5	220 / 1 / 28 / 5.5	220 / 1 / 28 / 5.5
Air Pressure / Cons. PSI/CFM	90 / 2.5	90 / 2.5	90 / 2.5	90 / 2.5
Machine Dimensions LxWxH	72 x 63 x 53	88 x 89 x 58	94 x 99 x 59	118 x 113 x 58



www.advantage-machinery.com Ph: (305) 593-9030 Fax: (305) 593-9031
 e-mail: sales@garridousa.com 7258 NW 66th St Miami, FL 33166 USA