

Auto Side Seale USA-004B



Auto Side Sealing Machine, standard model USA-004B can adjust its packaging height basing on product to have strong seal & nice look. USA-004B adopted constant heating sealing knife by SSR control to keep stable temperature, power saving and easy change. POF is recommended to work with. USA-004B can reduce the film wastage & seal multiple length without any limitation. Simple design, easy operation, film saving & high efficiency, it is the latest model of wrapping machine.

Features:

- USA-004B can pack products with any length allowing user to have more working options.
- Packaging height & width can be adjusted by different sizes of products to enhance working efficiency.
- The memory sets in HMI can help user set up varied working parameters with quick & easy changing size.
- Most mechanisms are made of Modularization without welding, so machine is easy to dismantle for repairing & maintenance.
- The forming system makes bag fitting with product to save material & reduce wastage, so it can save film cost.
- Feature of BOX-motion help save sealing time and raise up packaging speed.
- Screen of HMI shows sign of machine problem & instruction of troubleshooting; it help worker fix machine quick without needing to find worker's manual.
- Adopted continuous MD sealing design without length limitation.
- Sealing size: No limitation length of MD seal x TD 350mm seal (L x W)

Specification:

- Power: 3Ø 220V 50/60HZ
- Machine Dimension: 2400 x 1300 x 1730 (m/m)
- Sealing Bar Length: ∞ x 350 (m/m)
- Max. Package Height: H 5 - 150 (m/m)
- Heater: MD - 0.18 (KW), TD - 0.5 (KW)
- Motor: 1/2 HP x 1, 1/4 HP x 1, 1HP x 1.15W x 1, 40W x 1
- Packaging Capacity: 60 (Boxes/Min), Box: 180 x 110 x 42 (m/m)
- Air Pressure Required: 5.5 (80psi) KG/cm²