

GPZ30-1N A

预灌封注射器真空灌装加塞机

Prefillable syringes vacuum filling and closing machine



适合预灌封注射器，水剂、膏剂粘稠药液灌装。
 For prefillable syringes, suitable for filling water-based solution, poultice, viscous liquid, gel.

主要技术参数 Main Technical Parameter

适合注射器容量 Syringe volume	0.5-50ml
灌装范围 Filling volume	0.05-50 ml
灌装精度 Filling accuracy	≤ ±0.3%
注料针数量 Filling nozzles	1支 (Pc)
速度 Speed	900-1200支 / 小时 (Pcs/hour)
主机总功率 Total power	2.7 Kw
压缩空气 Compressed air	0.55-0.75 Mpa 20L/S
外配真空泵 Vacuum pump	6X10 ⁻² Pa 15L/S 1.5Kw
外形尺寸 (长 × 宽 × 高) Overall dimension (L × W × H)	1200 × 9500 × 1800 mm
主机质量 Weight of basic machine	650 Kg



本机功能及特点 Functions and features

- 手工上注射器盒。
- 自动脱巢，自动盒分离。
- 自动上管，分管入杯。
- 自动随动注料，自动真空加塞（外配真空泵）。
- 灌装后的液体及注射器内无气泡。
- 可选配层流罩。
- 本机可单机使用，也可组成整套流水线。
- To load syringe tubs by hand.
- Automatically unloading of the nest with syringes from the tub, automatically push away the tubs.
- Automatically loading the syringes to the machine from the nest.
- Automatically plug-in type filling, to insert stoppers under vacuum condition (equipped with a set of vacuum pump) automatically.
- No air bubbles inside the filled syringes
- Can be equipped with LAF hood.
- This machine can be used as a individual machine, it can also form a multifunctional production line.