

LK-790C Full Automatic Side-wrap Capping Machine (With Conveyor)



Side-wrap Capping Machine is used for all kinds of metal, glass and plastic bottles, which with the exceptions of crowns, ROPP (Roll-on Pilfer Proof) and straight wall corks style closures. It is suitable for tightening standard flat caps, trigger spray caps, pump caps, spray caps, finger pump spray caps, cream dispenser caps, cream pumps, dispensing caps, dispensing pumps, foam dispenser pumps, atomizers, essential oil sprayers, cologne sprayers, lotion pumps, lotion caps, lotion dispensers, scent sprayers, fragrance pumps, fragrance sprayers, treatment pump caps and many more.

Our Side-wrap Capping Machine provides outstanding repeatable torque accuracy ensuring a high quality closure for every cap that it tightens. It designed to eliminate the strain and fatigue of hand capping, and which is a customer favorite for a very simple reason-it makes capping easy.

Features:

- No complex parameters need to set.
- Intuitional and human design of control interface.
- Easy learning and operating for un-technique user.
- Heavy Duty 304 Stainless Steel / Aluminum Frame.
- Use for any style of screw-on caps from standard to trigger spray.
- Loading/Conveying Direction: Left to right if facing front of machine.
- Air supply (2HP+) required for pneumatic operation. The compressor not provided & buyer must have own.

Specifications:

- Voltage: 220VAC 50/60Hz Single phase 1A.
- Pneumatic supply: 6~8 kg/cm².
- Variable Speed Conveyor
 - ▲ Conveyor Length: 1.5 meters.
 - ▲ Conveyor Belt: Width 100mm plastic chain.
 - ▲ Loading/Conveyor Height: 800±50mm from floor.
 - ▲ Speed of Conveyor: 0-12m/min. (Adjustable as required)
 - ▲ Standard model can be custom-made to meet the requirement of any bottle specification.
- Side-wrap Capping Machine
 - ▲ Tightens caps from 20mm to 120mm.
 - ▲ Torque range is adjustable as required.
 - ▲ No Chuck needs to change for larger or smaller cap.