



ZTV-150 Automatic Premade Bag Vacuum Packaging Machine



Our ZTV-150 automatic vacuum packing machinery unit for rice is composed of automatic electronic weighed, vacuum packaging machine, Z type bucket elevator, incline bucket and product conveyor and more.

The functions of ZTV-150 include automatic feeding, weighing, vacuum packaging, sealing, and printing, counting, punching and finished product conveying. It adopts PLC control apparatuses which are imported from well-known international companies. Thus, they are of reliable performance. The finished products done by automatic vacuum packing machine are of magnificent appearances.



Machine feature:

- Adopt advanced PLC from Germany Siemens, mate with touch screen and electric control system; the man-machine interface is friendly.
- Frequency conversion adjusts the speed: this machine uses frequency conversion equipment, can be adjusted within the range according to the needs of reality in production.

- Automatic checking: no pouch or pouch open error, no fill, no seal. the bag can be used again, avoid wasting packing materials and raw materials.
- The width of the bags could be adjusted by electrical motor. Press the control-button could adjust the width of clips, easily operate, and save time.
- Horizontal conveyer style to giving bag: it can put on more bags on the bag storage and have a low requirement about the quality of bags.

Technical parameters:

| Model | ZTV-150 |
|----------------------------|---|
| Measuring range | 500-2500g |
| Measurement accuracy | ±0.2-2% |
| Bag Type | Vacuum & Reseal Brick Bag |
| Operation Mode | Intermittent |
| Speed | Up to 8 bags/min |
| Bag Length | 80-150 mm |
| Bag Width | 50-80 mm |
| Bag High | 200-360 mm |
| Film Thickness | 0.04-0.12 mm |
| Voltage | AC 220V/ 50HZ, 1phase or per customer needs |
| Power Consumption | 5.5KW |
| Compressed Air Requirement | 0.6MPa, 0.36 M3 / Min |
| Weight | 2000KG |
| Dimension | 2500x1900x2700mm (L x K x G) |

