

RL 320 Vertical Automatic Packaging Machine



Features:

- > Equipped with security protection, in line with corporate safety management requirements;
- > Intelligent temperature controller, temperature control accuracy; to ensure that the sealing beautiful, smooth;
- > PLC servo system, pneumatic control system, large display touch screen constitute the driving control core; to maximize the control of the machine accuracy, reliability and intelligence;
- > The machine and the measurement configuration can automatically complete the measurement, feeding, filling bag, date printing, inflatable (exhaust), finished product delivery of all packaging process, and automatically complete the count;
- > Touch screen can store a variety of different product packaging process parameters, when the product can be used at any time without the need to re-set;
- > With a fault display system failure to help troubleshooting in a timely manner;
- > According to customer needs made of pillow-shaped bags, hanging whole bags;
- > Can have all stainless steel models and carbon steel spray model;
- > Single belt transport film, fast and smooth, small friction, less loss;
- > There are stainless steel models and carbon steel spray model selection.

Optional device:

- > Package or multi-pack with short packet cut off function;
 - > Hook whole function (can play round holes and a variety of irregular holes);
 - > Supporting discharge conveyor;
 - > Various automatic or semi-automatic metering conveyor;
 - > Inflation and exhaust function;
- Compressed air systems and nitrogen generators.

use:

> Suitable for irregular block and granular materials, such as candy, puffed food, small biscuits, roasted seeds and nuts, sugar, and milk powder, milk tea, starch, seasonings and so on.

Model	RL 320
Packing speed	40-90packs/min
Packaging film width	110-320 (mm)
The bag size	Long (80-180 mm) wide 45-150 - mm (mm)
The total power	3Kw
Heating power	Seal in the 0.7 Kw;The 1.2 Kw
The weight	350Kg
The machine noise	75 decibels or less
Overall dimensions	(length x width x height) 1220 * 900 * 900 (mm)
The compressed air consumption	6-8Kg/m2 0.3m3/min
Power source type	220V、50Hz