



SP-260C Pillow Packing Machine



Main feature:

1. Double inverter control, the bag length is set and cut, there is no need to adjust the air go, in one step, saving time and film.
2. Man-machine interface, convenient and quick parameter setting.
3. Fault self-diagnosis function, fault display at a glance.
4. High-sensitivity photoelectric eye color tracking, digital input sealing position, make sealing position more accurate.
5. Temperature independent PID control, better suited to a variety of packaging materials.
6. Positioning stop function, no sticking knife, no waste film.
7. The transmission system is simple, the work is more reliable, and maintenance is more convenient.
8. All controls are implemented by software, which facilitates functional adjustments and technical upgrades and never lags behind.

Application scope:

It is suitable for packaging of soft, long strips and loose objects such as towels, tissues, noodles, egg rolls, sausages, squid, popsicles, fudge, biscuits and fresh fruits.

Performance parameters:

Size	SP-260C
Film width	Max.260mm
Bag length	65~190mm or 120~280mm
Bag width	30~110mm
Product height	Max.40mm
Film roll diameter	Max.320mm
Packing speed	40~230 bags/min
Power Specifications	220V, 50/60HZ, 2.4KVA
Machine size	(L)3920×(W)670×(H)1320
Machine quality	800Kg