

Automatic Haldi Turmeric Powder Packing Machine CK-ZC420F



This turmeric powder packing machine is the latest powder packaging machine series of our company, which is specially designed and manufactured for powder and ultra-fine powder materials. The haldi packing machine adopts intelligent numerical control system, microcomputer PLC control, and equipped with high-precision servo motor/stepper motor, stepper motor pull bag, bag length consistency is high, stable and reliable performance.

The filling mechanism of the turmeric powder packing machine uses stepping motor to drive feeding screw to ensure the accuracy of measurement. sealing and cutting in one, ensure the width of the transverse seal without error; Double-sided heating, very suitable for composite film packaging materials. The haldi packing machine can ensure that each package pattern is in the same position, and can automatically determine the length, positioning and speed regulation, no material or stuck material automatically stop.

Turmeric Powder Packing Machine Features:

- All stainless steel exterior, meet GMP requirements, reasonable design, simple structure.
- Stepper motor control, convenient and accurate bag length setting.
- The speed adjustment is simple, fast, stable and accurate.
- Display screen operation, easy adjustment, high degree of automation.
- The haldi packing machine uses advanced photoelectric number control bag system, lower film is stable and accurate, bag length can be directly set on the operating surface.
- Cursor on the version, you can get accurate logo patterns.

Turmeric Powder Packing Machine Performance Advantages:

1. Stepper motor pulling film, screen adjustment parameters, easy to operate.
2. Strong expansion function can increase the inflatable device, to meet the needs of different products.
3. Bag making, filling, measuring, sealing, printing date, product output completed in one time.

Model	CK-ZC420F
Air consumption	2.5m ³ /min.6kg/cm ²
Max. film width	120-380mm
Bag length	80-240mm
Bag width	50-180mm
Max. film roll diameter	Max.300mm
Packing speed	5-70bags/min
Packing thickness	0.04-0.08mm
Power supply specification	220V.50/60Hz.2.4KVA
Dimension	(L)880*(W)810*(H)1350mm
Total weight of machine	350kg