

Smart Weigh SW-P460 Quad-sealed Bag Packing Machine



Features:

- Mitsubishi PLC control with stable reliable biaxial high accuracy output and color screen, bagmaking, measuring, filling, printing, cutting, finished in one operation;
- ♦ Separate circuit boxes for pneumatic and power control. Low noise, and more stable;
- Film-pulling with servo motor double belt: less pulling resistance, bag is formed in good shape with better appearance; belt is resistant to be worn-out.
- ♦ External film releasing mechanism: simpler and easier installation of packing film;
- Only control touch screen to adjust bag deviation. Simple operation.
- ◇ Close down type mechanism, defending powder into inside of machine.

Suitable for many kinds of measuring equipments, puffy food, shrimp roll, peanut, popcorn, cornmeal, seed, sugar and salt etc. which shape is roll, slice and granule etc.

Parameters:

Model	SW-P460
Bag size	Side width: 40- 80mm; Width of side seal: 5-10mm
	Front width: 75-130mm; Length: 100-350mm
Max width of roll film	460 mm
Packing speed	50 bags/min
Film thickness	0.04-0.10mm
Air consumption	0.8 mpa
Gas consumption	0.4 m3/min
Power voltage	220V/50Hz 3.5KW
Machine Dimension	L1300*W1130*H1900mm
Gross Weight	750 Kg