

## *HXJ type of active oil bottle washing machine*



### **Purpose and brief:**

This machine is suitable for a small jar of cleaning is based on a special plate to a bottle carrier turnover cleaning equipment. Bottle upside down to be washed every dish in turnover to put bottles of holes, each plate 40. Bottle will be placed into the cleaning tank revolving plate, push to the required position, PLC control cylinder to accomplish the following: push down the revolving plate rack - lifting frame down to cleaning position (automatic cleaning needle into the bottle) - back to the first spray of water (the length of time set on the touch screen) - stop back to the water spray air purification (time configurable) - stop spraying compressed air purification clean water (time can be set) - stop spraying purified water purifying compressed air (time can be set) - to stop gas, auto lift rack up - working disk is automatically pushed into the box flip - flip box 180 degrees - flip box revolving disk was introduced - turnover rose plate, leave the bottle in the collection tray - air flow plate rack was introduced, recycling.

### **Main technique parameters:**

Suitable bottle: active oil bottle holes (diameter up to  $\phi 3.5\text{mm}$ )

Production capacity: 120 ~ 160 bottles / min

Back to the water consumption: 0.5m / h Pressure: 0.25 ~ 0.3 MPa

Purified water consumption: 0.5m / h Pressure: 0.20 ~ 0.25MPa

Clean air consumption: 0.6m / min Pressure: 0.30 ~ 0.4MPa

Power supply: 380V 50Hz

Power: 2Kw

Dimensions: 2500×1650×1450