

Computer control fast pillow packaging machine ZH-H100



Features

- Dual frequency conversion control, Bag length can be set and cut in one step, Saving time and film.
- Reasonable construct. stable working performance. and PLC computer control . easy operation . Self fault diagnosis , Clear fault display .
- High sensitivity photo cell color tracing. numerical input of cutting and sealing position for extra accuracy. Positioned stop function, without sticking knife or wasting film.

Applications

Packaging various kinds of regular objects like biscuits. Bread. egg roll, instant noodle. moon cake. medicine. hardware. industrial parts, paper boxes, plates. etc.

Technical Parameters:

Туре	ZH-H100	ZH-H100A
Film width	90-250mm	
Bag-making length	65-190 or 120-280mm	90-220mm
Bag-making width	30-110mm	
Production height	Max.40mm	Max.60mm
Film roll diameter	Max.250mm	
Packing material	OPP,PE,PVC,OPP/CPP,KOP/CPP,ALU-FOIL	
Thickness of film	0.03-0.07mm	
Packaging speed	40-230bag/min	
Power specification	3.4KW /220V, 50/60Hz,	
Machine Dimension	(L)3770 x (W)640 x (H) 156mm	
Machine weight	500kg	
Optional device	Printer, Air-filling device, Feeder, Tidier, alcohol spray device	