



ZHTBS02 Adhesive Front And Back Labeling Machine



Product Description

1. Double side labeling for rectangular, square bottles, and elliptical bottles.
2. Controlled by computer (PLC) and touch screen control panel, so to achieve easy operating.
3. With volume of 0 to 5L.
4. Labeling speed range : 0~26 meter/minute

Major Characteristics:

1. This labeling machine is suitable for foodstuff, cosmetic, pharmaceutical, pesticide and other lines.
2. Double side labeler for rectangular bottles and square bottles. It is automatically controlled by computer (PLC) and touch screen control panel, so to achieve easy operating.
3. If there is no bottle, it will not label. More than ten groups of labeling parameters can be memorized.
4. The specifications can be easily changed. Servo motor helps to realize closed-loop control. It has advantages like low malfunction rate and high efficiency as well as fast speed.

Main Performance Parameter:

1. Power supply : AC220V ;50Hz (or according to client voltage requirement)
2. Power : 3kw
3. Labeling speed range : 0~26 meter/minute
4. Suitable label roll inner Diameter size : $\Phi 75\text{mm}$
5. Suitable label roll outside Diameter size : $\Phi 350$ Maximum
6. Standard label high size : 300mm
7. Maximum label high size : 300mm
8. Machine weight : 750kg
9. Machine dimension (L \times W \times H): 3000mm \times 1200mm \times 1600mm