

DXD-series Fully-Automatic Weighting Packing Machine



Suitable for automatic packaging particle materials like all kinds of food, potato chips, shrimp, sweets, chocolate, biscuits, peanuts, nuts, rice, grain, seeds, pistachio, coffee, beans, lima beans, jelly, frozen food, chicken essence, suger, salt, etc.

Feature:

- 1) Import PLC control system, simple-operating, visual touch screw.
- 2) Servo film feeding system, correct register sealing and cutting positions adopt automatic correction device, high automation.
- 3) Intelligent temperature controller is used, correct temperature control, ensure nice, smooth seal.
- 4) Perfect automatic alarming protective function, reduce the consumption up to the lowest.
- 5) When the machine is combined with metering equipments, full packaging process including automatic feeding, metering, bag filling, date printing and automatic counting is completed.
- 6) Type of bag making: Can be coustomerd, like: Pillow bags, punched hanging bags.

Technical Parameters:

Automatic weighting packing machine	DXD-420C	DXD-520C
Packing speed (s/min)	15-70bags/min	15-70bags/min
Bag-making size (mm)	(L)80-300mm(W)80-200mm	(L)80-350mm(W)80-250mm
Filling range (g)	10-2000g	10-3000g
Packing meterials	OPP/CPP PET/PE PET-AL/PE etc.	OPP/CPP PET/PE PET-AL/PE etc.
Film width (mm)	180-420mm	180-520mm
Film thickness	0.04-0.08mm	0.04-0.08mm
Air consumption	0.36m3/min 0.6Mpa	0.36m3/min 0.6Mpa
Power supply	AC220V/380V 50/60Hz 3.5KW	AC220V/380V 50/60Hz 3.5KW
Machine dimension (mm)	L*W*H=1750*1050*1500-2000	L*W*H=1750*1350*1650-2000
Machine weight (kg)	500Kg	650kg

Automatic weighting packing machine	DXD-620C
Packing speed (s/min)	15-60bags/min
Bag-making size (mm)	(L)80-400mm(W)80-280mm
Filling range (g)	50-5000g
Packing meterials	OPP/CPP PET/PE PET-AL/PE etc.
Film width (mm)	180-600mm
Film thickness	0.04-0.10mm
Air consumption	0.6m3/min 0.6Mpa
Power supply	AC220V/380V 50/60Hz 4.5KW
Machine dimension (mm)	L*W*H=2150*1400*1750-2000
Machine weight (kg)	800kg