

*Pillow type packaging machine BCSZ150-01 (upper roll film)
BCXZ150-02 (lower roll film)*



Pillow packaging machine using roll film bag-making, widely used in the packaging of various bag products; the main models are standard, wide, high-speed, back-seal, shrink film and other models.

Upper roll film range of application: cookies, bread, instant noodles, moon cakes, candy, drugs, daily necessities, hardware accessories, cartons or trays and other solid and regular objects packaging.

The lower roll film is applicable to: towels, paper towels, dry noodles, egg rolls, sausages, squid, popsicles, fudge, cookies, fresh fruits and other soft, long and loose packaging.

Features:

- Double inverter control, bag length can be set and cut at one time, no need to adjust idling, one-step, save time and film.
- Touch screen human-machine interface, convenient and quick parameter setting.
- Fault self-diagnosis function, clear fault display.
- Imported photoelectric color code tracking, touch screen setting sealing and cutting position, so that the sealing and cutting position is more accurate.
- Independent PID control temperature, better suitable for various packaging materials.

- Positioning shutdown function. Special coating of cutting knife, non-stick knife, strong and durable.
- Simple transmission system, more reliable, more convenient for maintenance.
- All controls are realized by PLC, easy for function adjustment and technology upgrade.
- Various accessory devices and automatic feeding devices can be added.

Technical Parameters:

Model	BCSZ150-01 (upper roll film)	BCXZ150-02 (lower roll film)
Packaging Speed	10~120bag/min	10~120bag/min
Film width	Max : 250mm	Max : 250mm
Bag-making length	65~280mm	65~280mm
Bag making width	30~110mm	30~110mm
Product size	W : 140mm H : 30mm	W : 120mm H : 100mm
Roll diameter	Max : 320mm	Max : 320mm
Voltage	220/110V 50/60HZ	220/110V 50/60HZ
Power	3KW	3KW
Barometric pressure	0.5~0.8MPA	0.5~0.8MPA
Machine quality	800Kg	800Kg
Machine dimensions	L:3500mm W:1500mm H:1700mm	L:3500mm W:1500mm H:1700mm